Universal. Robust. Precise. High Speed.

Laser Receiver 5 T R L C T R

Twice as good.

Universal Laser Receiver Structor STR-60RG for red and green Rotation- and Line Lasers



























Premium Laser Receiver.

Made in Germany.



Laser Detection at its Best

Development, production and distribution:

AndroTec GmbH Hauptstraße 186 D-67714 Waldfischbach-Burgalben Tel. +49 (0) 6333 27 55-0, Fax -22 info@androtec.com, www.androtec.com



Technical Specifications Structor STR-60RG

Range with rotating lasers	Up to 400m (radius)
Range with line lasers	Up to 100m (only pulsed laser lines)
Capture height	60mm
Reception angle	±45°
Wavelength	450nm to 800nm
Pulse frequency of line laser	7kHz to 12kHz
Accuracy	±0,3mm / ±1mm / ±2mm / ±5mm
First Strike detection	Yes
Filter against	Flash / sun light / LED / fluorescent lamps
Beeper volumes	High (>100dBA) / low (75dBA) / off
Automatic shutoff	After 30min without key stroke / laser reception
Power supply	1 x AA
Battery life	>50 hours of continuous operation
Magnets	Neodymium
Protection class	IP67 (waterproof)
Physical dimensions	135mm x 69mm x 25mm
Weight without clamp	0,19kg
Operating temperature range	-10°C to +50°C
Storage temperature range	-40°C to +70°C

57

Structor STR-60R is compatible with almost all red and green rotation and line lasers. Please ask us. We'll tell you whether Structor is compatible with your laser.





User-friendly: Displays front and rear



Eco-friendly and moneysaving: Requires only one AA battery!